

Technical parameters of toroidal transformers

Type	Nominal power	Dimensions (mm)	Weight (kg)	Recommended safety fuse
EHT20-H	20 VA	Ø 69 x 31	0, 40	250V/ 200 mA/T
EHT25-H	25 VA	Ø 71 x 32	0, 42	250V/ 200 mA/T
EHT30-H	30 VA	Ø 72 x 36	0, 45	250V/ 400 mA/T
EHT50-H	50 VA	Ø 84 x 39	0, 71	250V/ 400 mA/T
EHT63-H	63 VA	Ø 86 x 49	1, 04	250V/ 630 mA/T
EHT75-H	75 VA	Ø 86 x 49	1, 04	250V/ 630 mA/T
EHT100-H	100 VA	Ø 115 x 44	1, 47	250V/ 1 A/T
EHT120-H	120 VA	Ø 113 x 41	1, 52	250V/ 1,25 A/T
EHT150-H	150 VA	Ø 115 x 47	1, 67	250V/ 1,25 A/T
EHT160-H	160 VA	Ø 115 x 47	1, 84	250V/ 1,25 A/T
EHT200-H	200 VA	Ø 113 x 53	2, 08	250V/ 2,5 A/T
EHT250-H	250 VA	Ø 114 x 55	2, 20	250V/ 3,15 A/T
EHT300-H	300 VA	Ø 136 x 47	2, 78	250V/ 3,15 A/T
EHT400-H	400 VA	Ø 138 x 54	3, 40	250V/ 4 A/T
EHT500-H	500 VA	Ø 152 x 52	4, 15	250V/ 5 A/T
EHT630-H	630 VA	Ø 154 x 65	5, 20	250V/ 6,3 A/T
EHT750-H	750 VA	Ø 155 x 66	5, 40	250V/ 6,3 A/T
EHT1000-H	1000 VA	Ø 168 x 76	7, 00	250V/ 10 A/T
EHT1200-H	1200 VA	Ø 186 x 66	7, 60	250V/ 12 A/T
EHT1500-H	1500 VA	Ø 188 x 76	9, 30	250V/ 12 A/T
EHT2000-H	2000 VA	Ø 220 x 88	12, 50	250V/ 16 A/T
EHT2500-H	2500 VA	Ø 250 x 90	15, 20	250V/ 16 A/T
EHT3000-H	3000 VA	Ø 265 x 92	17, 90	250V/ 16 A/T

Fixing accessories:

20-30VA Ø50 mm, fixing with M5 screw

50-1000VA Ø74 mm, fixing with M6 screw

>1000 VA Ø112 mm, fixing with M8 screw